

Haugen

★ **Work Platforms**

★ **Truss Jibs**

877-580-6218



Marv Haugen Enterprises Inc.

P.O. Box 868 • Casselton, ND 58012 • Phone: 701-347-4827 • Fax: 701-347-4830

Website: www.haugenattachments.com • E-mail: haugen@equipitnow.com

Features

- Heavy duty steel mesh floor for years of dependability
- Safety restraint tie down bar is standard on all Platforms
- Industrial hinges and latches for strength and safety
- Door Safety Pins allow the door to remain rigid and strong
- Easily pins onto your machines
Fork Tines
- Safety pins secure side rails and doors
- Meets and/or exceeds OSHA Standards



Safety Features



Safety Pins are standard for all doors and side rails. Each pin is attached to the rail by a cable to prevent losing the safety pins



Door Safety Pins gives the door extra strength and allows the door to remain rigid at all times



Safety Restraint Tie Downs are standard on all platforms. This gives you a safe place to connect your safety harnesses



Optional End Forks Slots make it easy to transport your Platform. To be used for loading and unloading only



Pins over your Fork Tines Each pin is chained to the Platform. Fits to most Telehandlers



Collapsible
for easy transportation

SPECIFICATIONS

Model Number	Size	Capacity	Weight
MWP 4x4	4x4	1000 LBS	360 LBS
MWP 4x6	4x6	1000 LBS	460 LBS
MWP 4x8	4x8	1000 LBS	531 LBS
MWP 4x116	4x9'8"	1000 LBS	591 LBS
MWP 4x122	4x10'2"	1000 LBS	615 LBS
MWP 4x12	4x12	1000 LBS	750 LBS

Custom sizes available upon request.

Haugen
Taking Platforms to new Heights

Think Quality
Think Safety
Think Haugen

www.haugenattachments.com



Industrial Jibs

*Fits on most types of Forklifts
mounts to your fork tines*







**Manually adjusts from 6'9" to 12 feet
with 9 different positions**

*Lift Capacity Rating

Jib Position	Length	*Max Lift Capacity
1	78.00 inches	6000 LBS
2	86.00 inches	5715 LBS
3	94.00 inches	5410 LBS
4	102.00 inches	5075 LBS
5	110.25 inches	4710 LBS
6	118.50 inches	4320 LBS
7	126.75 inches	3905 LBS
8	135.00 inches	3465 LBS
9	143.25 inches	3000 LBS





* These lift capacity ratings are for the Industrial Jib only. The lifting capacity is ultimately determined by the host machine.

Truss Jibs

-  Quick Attach Truss Jibs for Telehandlers
-  Custom built to fit your machine
-  2000 LBS lift capacity
-  Available in 12 and 16 foot lengths



Fork Slot Jibs

-  Fork Slot Truss Jibs for Telehandlers, Fork Lifts,
and Loaders
-  2000 LBS lift capacity
-  Mounts to your fork tines
-  Available in 12 and 15 foot lengths

